







Model	DJ-03HD	MP100	MP110	MP 150	MP 200	MP 300	MP 500
Headshell-Befestigung	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll
System Typ	MM	MM	MM	MM	MM	MM	MM
Frequenzgang (Hz)	20-20.000 ± 2dB	20-20.000 ± 2dB	20-20.000 ± 2dB	20-20.000 ± 2dB	20-23.000 ± 2dB	20-25.000 ± 2dB	20-25.000 ± 2dB
Ausgangs-Spannung (mV)	6.0 @ 5 cm/sec	5.0 @ 5 cm/sec	5.0 @ 5 cm/sec	4.5 @ 5cm/sec	4 @ 5cm/sec	3 @ 5 cm/sec	3 @ 5 cm/sec
Kanaltrennung (dB)	20 typisch 1 kHz	22 typisch 1 kHz	23 typisch 1 kHz	24 typisch 1 kHz	25 typisch 1 kHz	25 typisch 1 kHz	27 typisch 1 kHz
Kanalungleichheit (dB)	>2.0	>2.0	>1.5	>1.5	>1.5	>1	>1
Cantilever	Aluminium alloy	Aluminium alloy	Aluminium alloy	Hard aluminium alloy	Boron	Boron	Born
Nadelschliff/Größe (mm)	0.5 mil conical bonded Diamant	0.5 mil conical bonded Diamant	0.3 – 0.7 elliptical bonded Diamant	0.3 – 0.7 elliptical Diamant	0.3 – 0.7 elliptical Diamant	0.3 – 0.7 super elliptical Diamant	Grain oriented line contact profile
Abschluss-Impedanz(Ω)	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K
Gewichtseinstellung (g)	4	2-2.5	1.8 – 2.3	1.8 – 2.3	1.5 - 2	1.5 - 2	1.3 – 1.8
Gewicht (g)	5.6	6.8	6.8	7.8	7.8	8	8
Besonderes	DJ Abnehmersystem	Dynamic Coil, für jede Musik geeignet	Dynamic Coil, für jede Musik geeignet	Hartaluminium Canti lever. Voll Diamant	Boron Canti lever. Voll Diamant	Boron Canti lever. Voll Diamant	Boron Canti lever. Voll Diamant line contact speziell Befestigung für Nadel.
Preise Systeme	115.00	150.00	190.00	480.00	550.00	940.00	1200.00
Preise Nadeln JN-P	Nicht mehr lieferbar	55.00	68.00	290.00	320.00	390.00	450.00

							
Modèle	DJ-03HD	MP100	MP110	MP 150	MP 200	MP 300	MP 500
Fixation	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll	½ Zoll
Type de système	MM	MM	MM	MM	MM	MM	MM
Réponse en fréquence hertz	20-20.000 ± 2dB	20-20.000 ± 2dB	20-20.000 ± 2dB	20-20.000 ± 2dB	20-23.000 ± 2dB	20-25.000 ± 2dB	20-25.000 ± 2dB
Tension de sortie (mV)	6.0 @ 5 cm/sec	5.0 @ 5 cm/sec	5.0 @ 5 cm/sec	4.5 @ 5cm/sec	4 @ 5cm/sec	3 @ 5 cm/sec	3 @ 5 cm/sec
Séparation typique des canaux (dB)	20 typisch 1 kHz	22 typisch 1 kHz	23 typisch 1 kHz	24 typisch 1 kHz	25 typisch 1 kHz	25 typisch 1 kHz	27 typisch 1 kHz
Différence entre canaux (dB)	>2.0	>2.0	>1.5	>1.5	>1.5	>1	>1
Cantilever	Aluminium alloy	Aluminium alloy	Aluminium alloy	Hard aluminium alloy	Boron	Boron	Born
Taille / meulage d'aiguille	0.5 mil conical bonded Diamant	0.5 mil conical bonded Diamant	0.3 – 0.7 elliptical bonded Diamant	0.3 – 0.7 elliptical Diamant	0.3 – 0.7 elliptical Diamant	0.3 – 0.7 super elliptical Diamant	Grain oriented line contact profile
Impédance finale	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K	47.0 K
Pression de lecture (g)	4	2-2.5	1.8 – 2.3	1.8 – 2.3	1.5 - 2	1.5 - 2	1.3 – 1.8
Poids (g)	5.6	6.8	6.8	7.8	7.8	8	8
Particularités	DJ	Coil, dynamique adapté pour chaque musique	mais avec. une taille affinée pour une meilleure definition.	Alu cantilever, Diamant compl.	Boron Canti lever. Diamant compl La coupure elypt. garantit une meilleure qualité de reproduction	Boron Canti lever. Diamant compl La coupure elypt. Super fin garantit une meilleure qualité de reproduction	Boron Canti lever. Diamant compl La coupure line contact garantit une meilleure qualité de reproduction
Preise Systeme	115.00	150.00	190.00	480.00	550.00	940.00	1200.00
Preise Nadeln JN-P	discontinued	55.00	68.00	290.00	320.00	390.00	450.00